PD240C

NEW GENERATION LONG RANGE HAND HELD METAL DETECTION SET

FEATURES

- Very High Penetration
- Exceeding the NIJ Standard 0602.02 detection requirements
- Large Search Area
- Accurate pinpointing
- Uniform Detection of Magnetic and Non-Magnetic Targets
- Full Digital Design: Consistent Performance and Calibration-Free Operations
- Elegant, Robust and Ergonomic
- Indoor and Outdoor Operations



PD240C Hand Held
Detection Set with carry bag







GSA Contract Holder

www.ceia-usa.com

Threat Detection through Electromagnetics

cela.net



The PD240C is a Hand Held Metal Detector that combines high reliability and ergonomics with advanced detection and operator signaling features. Deep penetration for weapons and minimum metal targets, effective sensitivity to all alloys, exceeding the latest Security Standards and high immunity to external metal masses are among the main peculiarities of this new device.

Advantages & Benefits

- Programmable Sensitivity
- Long Detection Range
- Extended Continuous Operation Time
- Automatic Low Power Mode during Screening Pauses
- Embedded Long Life Rechargeable Batteries are renewable energy and wipe out Operation Cost of Alkaline Batteries
- Embedded Fast and Reliable Battery Charger: no need of batteries removal
- Dedicated Holder acts as Minimum Space Table Stand and Mains connection for Battery Charge
- Operator Functions can be standard or customized by the user through PC GUI and USB connection



Long Detection Range

✓ Elegant, Robust and Ergonomic

The PD240C features a special ergonomic design consisting of an offset hand grip which ensures that the operator's hand does not interfere with the sensitive detection area. Special care has gone into the mechanical design of the detector. Absence of sharp edges or corners allows the detector to be passed smoothly over the inspected area without getting caught in buttons, buckles, folds or other parts of clothing.

Control Panel & Alarm Buzzer



✓ NIJ standard 0602.02 Compliant

The technical features of the detector comply with and exceed the NIJ standard 0602.02 and the new NIJ draft standard 0602.03. The PD240C has uniform sensitivity to magnetic and non-magnetic targets including those made of stainless steel. At the same time the detector offers excellent body-effect compensation and has high immunity to external disturbance from electromagnetic and mechanical sources.

✓ Full Digital Design

The PD240C is fully digital. Electronic functions include a inspection field transmitter-receiver based on Digital Signal Processing (DSP) technology, a digital operator interface and external communications over the incorporated USB port.

Advanced Control Panel

The control panel with switches and warning lights is made from high-thickness silicon guaranteeing high degree of protection to make the PD240C suitable for indoor and outdoor use.

Mary Advanced Alarm Indication

The alarm signalling modes include: optical alarm which is fixed or is proportional to the intensity of the detection signal; acoustic alarm with a constant tone or a tone which is proportional to the size of the object detected; vibration alarm signal. It is also possible for the safety manager or the checkpoint supervisor to lock one or more operator commands.

✓ Extended Continuous Operation Time

The PD240C metal detector is powered by two AA-size NiMH batteries with a battery life of over 55 hours. A Low Power Mode is automatically activated during pauses, extending the battery life up to 100 hours. An internal circuit optimises battery recharging which takes less than five hours.

✓ Latest plastic materials technology

The metal detector casing is made from next-generation technical polymers. These plastics offer high chemical resistance and mechanical strength ensuring a long detector life even in heavy duty conditions.

Fully Programmable Signaling

- Proportional/Fixed, High Loudness Acoustic Alarm
- Proportional/Fixed, High Brightness Optical Alarm
- Vibration Alarm for Discrete Screening



- A Power push button
- B C Alarm Mode selection
- D E F Sensitivity selection:
 - Low Medium High
 - G Alarm indicator
 - Battery charge indicator







Optical indication proportional to the metal signal strength [Low, Medium, High]

Sophisticated Communication Capabilities

The digital design of the new metal detector also enables the maximum flexibility in selecting how detection alarms are signalled. Users can keep the factory settings or connect the detector over its USB to a PC and then personalise the settings with a dedicated graphic interface.



PD240C New Generation

Long Range Hand Held Metal Detection Set

Specifications

POWER SUPPLY	2x AA size NiMH, rechargeable batteries		
FULLY CUSTOMIZABLE	Optical, acoustic and vibration alarm modes 3-level sensitivity selection buttons		
CONTROL PANEL			
DETECTION AND OPERATIONAL FUNCTIONS	Customizable via HHMD Configuration tool		
BATTERY	Battery life	55 + hours continuous service (AA NiMH batteries 2500 mAh); up to 100 hours with automatic sleep mode	
	Low battery indicator		
	Built-in fast battery charger in combination with the HHDS Docking station		
OPERATING TEMPERATURE	-35°F to 158°F		
STORAGE TEMPERATURE	-35°F to 176°F		
RELATIVE HUMIDITY	0 to 98% (without condensation)		
DIMENSIONS	PD240C: 16" x 4.7" x 1.6"		
	HHDS Docking station: 6.9" x 4.5" x 3.4"		
	Carry Bag: 17" x 13	3.4" x 4.1"	
	Detection Set Pack	kage PD Set: 17.7" x 12.8" x 4.5"	
WEIGHT	PD240C (with batte	ry): 0.97 lbs	
	HHDS Docking station for PD240C (whit power adapter): 1.6 lbs		
	Carry Bag: 2.9 lbs		
	Detection Set Pack	kage PD Set: 4.8 lbs	
COLOR	PD240C: light grey RAL 7040 - Carry Bag: Green RAL 7013		
MANUFACTURED IN GREY SHOCK-RESISTA	NT TECHNICAL POLYME	RS	
COMPLIANCE	Conforms to the NIJ 0602.02 and the new NIJ 0602.03 Standards for metal detection		

applicable CE regulations







Conforms to the international standards currently applicable for safety, EMC and to the

PD240C Set inside the Carry Bag

Ordering Information

PD Set: part # PD240C-SET

Accessories

NIJ 0602.02 Test Pieces Kit: part # NIJ-HHMD-0602.02 (includes 11 test objects for LO, MO, SO, VSO security levels)

Carry Bag: part # 64082

HHMD Configuration tool: part # 63537 (includes special USB adapter with cable, GUI application software)

#	Part List - description

- 1 PD240C Hand Held Metal Detector
- 2 HHDS Docking station
- Coupling pins for HHDS side-by-side placement
- 4 Calibration NIJ compliant Test Piece
- Universal AC adapter
- 6 US, EU, UK, JP plugs adapter
- 7 Wrist strap
- 8 Instruction manual
- 9 Quick Reference Guide
- 10 Carry Bag



HHMD Configuration tool

Applications

✓ Airports

✓ Correctional Facilities

✓ Law Enforcement

✓ Government Buildings

✓ Nuclear Facilities

✓ Loss Prevention

✓ Public Events

✓ Schools Security



CEIA USA Ltd - 9155 Dutton Drive, Twinsburg, OH 44087 Phone: (330) 405 3190 - Fax (330) 405 3196 - e-mail: security@ceia-usa.com

DP100K0008V2000US